







Mulcher designed for tractors between 40 HP to 80 HP for the maintenance of vegetable mantle and for the elimination of remains of pruning up to 50 mm.

Special configuration for frontal works.

CHARACTERISTICS

- ► Steel-plate chassis, thickness 6 mm.
- ▶ Tubular rotor of Ø 400 mm.
- ► Gearbox with freewheel included.
- ▶ 4 XPB side belt transmission.
- ► Forged hammers SERRAT special "grass".
- ▶ 2 lines of counter knives screwed in.
- ► GIROSTOP System.

- ▶ Supports of bearing rotor in steel.
- ▶ High speed and high strength bearings.
- ► Rear hydraulic hood.
- ▶ PTO 540 rpm.
- ► Double bearing on rear roller.
- ► Model built under EC Normative.
- ► Safety indicators visible to personnel.



Gearbox



Detail of the roller



OPTIONS



► Hydraulic side shift

	MODEL				KG	N° BELTS TYPE							
_		mm	KW-HP				A mm	A in	B mm	B in	C mm	C in	
	T-1400	1400	34 - 45 60 - 80	12	397	4XPB	1595	63"	1155	45"	840	33"	540
	T-1600	1600	37 - 50 60 - 80	12	420	4XPB	1795	71"	1155	45"	840	33"	540
	T-1800	1800	45 - 60 60 - 80	16	456	4XPB	1995	79"	1155	45"	840	33"	540



22310 Castejón del Puente (Huesca)-España Tfno. (+34) 974 417 830 www.serrat.com - comercial@serrat.es





The data presented in this catalog are provided for information purposes only and are not binding.